



Model# SUA7500E

UPC Number: 616641364755



FEATURES

- * Long Life Overhead Valve Engine
- * Low-Oil Shutdown to Prevent Engine Damage
- * High Performance Alternator
- * Steel Fuel Tank With Fuel Gauge
- * Hardened Steel Tube Chassis
- * Never-Flat Wheel Kit
- * Fold-Down Handle
- * Circuit Breaker Protected Outlets
- * Weather Protected Outlets
- * Low Tone Muffler

Gasoline Portable Generator

Rated Output Watts	6000W
Maximum Output Watts	7000W
Rated Voltage	120V/240VAC
Frequency	60Hz
Rated Amperage	50/25A
Maximum Amperage	58.3/29.2A
Alternator	Senci
Engine Displacement	420 cc / 14HP
Engine Type	190FD OHV
Engine RPM	3600 RPM
Recommended Oil	SAE 10w30
Lubrication Method	Splash Sump
Choke Type	Manual Lever
Fuel shut Off	Manual Lever
Hour Meter	Yes - Digital
Starting Method	Electric/Manual Start
Battery	Yes
Battery Size	12VDC 12Ahr
Low Oil shutdown method	Automatically
Start Switch type	Push Start / Off
Switch Location	On Control Panel
Spark Plug	F7TC
Fuel Gauge	Yes - In Tank
Fuel Tank Capacity (Gal.)	7
Run Time @ 50% (Hours)	8.5hrs
Handle Style	Folding
Wheel Type	Solid Wheels
Maintenance Kit	Yes
Complaint	EPA
Sound Level (dB)	74dB
Assembled Length (in.)	27.5
Assembled Width (in.)	26
Assembled Height (in.)	26
Package Dimensions (L*W*H)(in.)	28.5X22X24
Net Weight (No Packaging)	195 Lbs.
Gross Weight (With Packaging)	204 Lbs.
Load Quantity 40'HQ/20' container	210ea/96ea
Load Quantity 53' Trailer	210ea
Pallet Quantity - 48"X40" Pallet	4ea (44"X29"X48")
Outlets:	4 - 120v 20R, 1 - Twist Lock 120v L5 - 30R, 1 - L14 - 30R 120/240v

NOTES: