

AE47

APPLICATION:
E4

LEGACY MODEL:
A2207

Code	Size	Ply	L.I.	Speed Rating	Rim in.	N.S. 32 ^{nds}	O.D. in.	S.W. in.	S.L.R. in.	R.C.	L.C.C. (1X) lbs.@psi	WT. lbs.
815337-74	23.5R25	**	185	B	19.50/2.5	59	65.0	23.6	29.3	196	20,400@76	827
815700-74	26.5R25	**	193	B	22.00/3.0	65	70.3	26.5	31.6	211	25,400@76	1,113
815352-74	29.5R25	**	200	B	25.00/3.5	72	74.6	29.5	33.5	225	30,900@76	1,429

RUBBER COMPOUND:	
CUT RESISTANT	<input type="checkbox"/>
HEAT RESISTANT	<input checked="" type="checkbox"/>
STANDARD	<input type="checkbox"/>

The Aeolus AE47 features multiple groove edges to provide excellent traction on all surfaces and terrain conditions.

Features and Benefits

- Extra-deep tread for exceptional tread wear and self-cleaning functionality
- Rugged shoulders minimize scrapes and punctures for maximum productivity
- Tread block designed for superior traction

Applications

- Articulated Dump Truck
- Rigid Dump Truck

