


Your Search: Name : LTX M/S2



LTX® M/S2

SUV/Crossover, Light Truck



Our Best-Selling Light Truck Tire.

The MICHELIN® LTX® M/S2 tire offers an exceptional combination of performances for light trucks and SUVs.

Benefits of This Tire:

- Stops Shorter for Added Safety
- Lasts up to 20,000 More Miles than Leading Competitors.²
- Better Snow Traction

Average User Rating:



Michelin Performance Ratings:

Wear Life 10/10	Fuel Efficiency 9/10	Off Road 7/10	Braking 8/10	Comfort 9/10

Tire Warranties:



Warranties



70,000 Mile Manufacturer's Treadwear Limited Warranty
LTX® M/S2 tires carry an additional 70,000 mile limited warranty for treadwear or mileage.

Available on:
LTX® M/S2
Speed Rating [R, T]



Standard Limited Warranty (All Michelin® Tires)
All Michelin® tires have a Standard Manufacturer's Limited Warranty, which covers defects in workmanship and materials for the life of the original usable tread, or for 6 years from date of purchase, whichever occurs first. See warranty for details.

TechSpecs

Part #	Tire Size	Load Index	Speed Rating	Sidewall	Ecology	Mileage Warranty	UTQG Treadwear, Traction, Temp	Rim Width Range (Min / Max)	Section Width (On Measuring Rim Width)	Overall Diameter	Revs Per Mile	Tread Depth (in 32nds)	Max Load, Single (@PSI)	Max Load, Dual (@PSI)	Tire Weight
36210	P235/75R15/XL	108	T	ORWL		70,000 Mile	720, A, A	6" - 8"	9.3" on 6.5"	28.9	721	12	1985@50	@	31.26
02397	LT215/85R16/E	115	R	BSW	Green X	70,000 Mile	.	5.5" - 7"	8.5" on 6"	30.4	684	13.5	2680@80	2470@80	39.46
11443	P225/70R16	101	T	ORWL		70,000 Mile	720, A, A	6" - 7.5"	9" on 6.5"	28.4	732	12	1654@44	@	30.23
07253	P235/70R16	104	T	ORWL		70,000 Mile	720, A, A	6" - 8"	9.5" on 7"	29	718	12	1804@44	@	31.26
33858	P235/75R16/XL	109	T	ORWL		70,000 Mile	720, A, A	6" - 8"	9.3" on 6.5"	29.8	697	12	2065@50	@	34.19
27679	LT235/85R16/E	120	R	BSW	Green X	70,000 Mile	.	6" - 7.5"	9.3" on 6.5"	31.7	656	13.5	3042@80	2778@80	43.19
19595	LT235/85R16/E	120	R	ORWL	Green X	70,000 Mile	.	6" - 7.5"	9.3" on 6.5"	31.7	656	13.5	3042@80	2778@80	43.28
35177	P245/70R16	106	T	ORWL		70,000 Mile	720, A, A	6.5" - 8"	9.8" on 7"	29.5	704	12	1904@44	@	34.59
21676	LT245/75R16/E	120	R	ORWL	Green X	70,000 Mile	.	6.5" - 8"	9.8" on 7"	30.5	683	13.5	3042@80	2778@80	41.89
28525	P245/75R16	109	T	ORWL		70,000 Mile	720, A, A	6.5" - 8"	9.8" on 7"	30.5	683	12	2065@44	@	34.66
11391	P255/65R16	106	T	BSW		70,000 Mile	720, A, A	7" - 9"	10.2" on 7.5"	29.1	716	12	1904@44	@	33.97
23111	P255/70R16	109	T	ORWL		70,000 Mile	720, A, A	6.5" - 8.5"	10.2" on 7.5"	30.1	691	12	2065@44	@	36.16
10302	P265/70R16	111	T	ORWL		70,000 Mile	720, A, A	7" - 9"	10.7" on 8"	30.6	679	12	2185@44	@	39.24
30217	LT265/75R16/E	123	R	ORWL	Green X	70,000 Mile	.	7" - 8"	10.5" on 7.5"	31.7	657	13.5	3415@80	3085@80	46.54
23388	LT265/75R16/E	123	R	BSW	Green X	70,000 Mile	.	7" - 8"	10.5" on 7.5"	31.7	657	13.5	3415@80	3085@80	46.27
00981	P265/75R16	114	T	ORWL		70,000 Mile	720, A, A	7" - 9"	10.5" on 7.5"	31.7	657	12	2365@44	@	40.43
21272	LT285/75R16/E	126	R	ORWL	Green X	70,000 Mile	.	7.5" - 9"	11.3" on 8"	32.8	634	13.5	3750@80	3415@80	52.82
01721	P235/70R17/XL	108	T	BSW		70,000 Mile	720, A, A	6" - 8"	9.5" on 7"	30	693	12	2005@50	@	32.1
17502	P235/75R17	108	T	BSW		70,000 Mile	720, A, A	6" - 8"	9.3" on 6.5"	30.9	674	12	2005@44	@	36.68
14157	LT235/80R17/E	120	R	BSW	Green X	70,000 Mile	.	6" - 7.5"	9.3" on 6.5"	31.8	654	13.5	3085@80	2835@80	43.43
91504	LT235/80R17/E	120	R	ORWL	Green X	70,000 Mile	.	6" - 7.5"	9.3" on 6.5"	31.8	654	13.5	3085@80	2835@80	43.41
00644	LT245/70R17/E	119	R	BSW	Green X	70,000 Mile	.	6.5" - 8"	9.8" on 7"	30.6	681	13.5	3000@80	2755@80	42.55
91940	P245/70R17	108	T	ORWL		70,000 Mile	720, A, A	6.5" - 8"	9.8" on 7"	30.6	681	12	2005@44	@	35.74
31733	LT245/75R17/E	121	R	BSW	Green X	70,000 Mile	.	6.5" - 7.5"	9.8" on 7"	31.5	660	13.5	3195@80	2910@80	45.46
18907	P255/65R17	108	T	ORWL		70,000 Mile	720, A, A	7" - 9"	10.2" on 7.5"	30.1	691	12	2005@44	@	35.49
00088	P255/70R17	110	T	ORWL		70,000 Mile	720, A, A	6.5" - 8.5"	10.2" on 7.5"	31.1	669	12	2125@44	@	36.82
25979	P265/65R17	110	T	ORWL		70,000 Mile	720, A, A	7.5" - 9.5"	10.7" on 8"	30.6	681	12	2125@44	@	37.57
14221	LT265/70R17/E	121	R	BSW	Green X	70,000 Mile	.	7" - 8.5"	10.7" on 8"	31.7	657	13.5	3195@80	2910@80	46.85
97723	LT265/70R17/E	121	R	ORWL	Green X	70,000 Mile	.	7" - 8.5"	10.7" on 8"	31.7	657	13.5	3195@80	2910@80	47.38
09607	P265/70R17	113	T	ORWL		70,000 Mile	720, A, A	7" - 9"	10.7" on 8"	31.7	657	12	3305@44	@	40.79
11305	LT285/70R17/D	121	R	ORWL	Green X	70,000 Mile	.	7.5" - 9"	11.5" on 8.5"	32.8	635	13.5	3195@65	2910@65	52.89
11631	P265/60R18	109	T	ORWL		70,000 Mile	720, A, A	7.5" - 9.5"	10.7" on 8"	30.5	682	12	2065@44	@	37.3
02633	P265/65R18	112	T	BSW		70,000 Mile	720, A, A	7.5" - 9.5"	10.7" on 8"	31.5	659	12	2245@44	@	39.26
28689	P265/70R18	114	T	ORWL		70,000 Mile	720, A, A	7" - 9"	10.7" on 8"	32.6	637	12	2365@44	@	40.87
79828	P275/65R18	114	T	ORWL		70,000 Mile	720, A, A	7.5" - 9.5"	11" on 8"	32.1	648	12	2365@44	@	41.42
01137	LT275/65R18/E	123	R	ORWL	Green X	70,000 Mile	.	7.5" - 9"	11" on 8"	32.1	648	13.5	3415@80	3085@80	51.04
04035	LT275/70R18/E	125	R	ORWL	Green X	70,000 Mile	.	7" - 8.5"	11" on 8"	33.2	627	13.5	3640@80	3305@80	52.01
22093	P275/55R20	111	T	BSW		70,000 Mile	720, A, A	7.5" - 9.5"	11.2" on 8.5"	31.9	652	12	2185@44	@	39.37
75433	P275/60R20	114	T	BSW		70,000 Mile	720, A, A	7.5" - 9.5"	11" on 8"	33	630	12	2365@44	@	40.87

1Based on wet braking test results for LT sizes versus Bridgestone® Dueler H/T 684 II tires and Goodyear® Wrangler® SA tires

2Based on third-party wear test results for P-Metric sizes versus Bridgestone® Dueler H/T 684 II tires and Goodyear® Fortera® TT tires.

OE Code [Original Equipment Key]: DC = DaimlerChrysler, F = Ford, HO = Honda, I = Infiniti, L = Lexus, MA = Mazda, N = Nissan, T = Toyota

* Passenger sizes used in Light Truck/SUV applications have reduced load capacity. This will differ from the maximum load branded on the tire sidewall.

Government UTQG Ratings do not apply to light truck sized tires.

XL = Extra Load

>> The sizes shown are average design values for tires measured on specified measuring rim widths. Some tires may vary from this value by +/-3% of the section height (affecting overall diameter), and +/-4% of the section width.

>> Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

>> Tread patterns are often tuned to accommodate different tire widths. Tires for a particular dimension of a given tireline may vary in appearance from the tire shown in the photograph.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on tire vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.

DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160km/h (100 mph), load and inflation must be adjusted according to the table below.

T-Speed Rated Sizes:

Maximum Speed (mph) 100 106 112 118

Inflation Increase (psi) 0.0 1.0 2.0 3.0

Load Capacity (% of max.) 100 100 100 100