



Model Number **SUA12000E**

Powerful, Portable, Tough, Compact, Reliable, Purpose-Built



Features


- 1) 12,000 Starting Watts / 9,000 Running Watts
- 2) 60Hz, 120VAC / 240VAC, Single Phase
- 3) Powerful 459cc/16HP Engine. Single cylinder, air-cooled, 4-stroke engine with electric start
- 4) High performance alternator provides greater peak wattage which allows motor driven appliances and tools to operate simultaneously.
- 5) Multiple Front Panel Outlets. Easy access, ergonomically angled compact control panel with multiple outlets with weather proof cover provides easy power connections and added protection from the environment and rugged working condition while conveniently providing easy, user-friendly access and visibility to the panel
- 6) Keyless one-touch push button provides an effortless start
- 7) Back-up recoil start. The oversized recoil ad ergonomically designed big grip reduces your effort to pull the recoil easily to start the engine.
- 8) Cast iron sleeves for engine durability and extended run life
- 9) Intelligent Automatic Voltage Regulator (AVR) helps minimize voltage fluctuations and deliver consistent stable power under load
- 10) 7.0 gallon, large heavy duty all steel construction fuel tank provides up to 9 hours of run time at 50% load
- 11) High quality, bright red, powder coat finish is attractive yet rustproof
- 12) Seamless welding prevents leakage while curved edges and corners provided added safety
- 13) Large built-in easy to read fuel gauge
- 14) Large Stainless steel fuel cap
- 15) Large counter-sink around fuel filling port prevents fuel overflow while filling
- 16) Fuel tank breather hose located beneath tank , provides added protection from accidental damage
- 17) GFCI Protected Outlets provides added protection and safety under damp condition
- 18) Digital Hour meter for monitoring runtimes and scheduling of maintenance intervals
- 19) Push to reset circuit breakers provide overload protection
- 20) Weather proof cover provides protection for Circuit breakers and receptacles
- 21) Built-in DC Adapter Plug. Built for charge your battery or use with your USB adapter to charge your cellphone.
- 22) Low oil shut down automatically protect engine from potential damage
- 23) Dual element air filter protects engine while allowing extended service interval
- 24) The cord protective cover keeps all the wires concealed while providing protection and neat appearance
- 25) Rigid low tone muffler. Compact heavy duty reinforced steel muffler helps minimize the noise level.
- 27) Neutral bonded to frame for added safety
- 28) 1.2in dia. rigid tubular steel frame with attractive silver grey powder coat finish
- 29) Built-in ergonomically designed handle provides easy transportation and folds down for compact storage
- 30) Effortless Move. Large 9.5in never-flat wheels designed for heavy duty loads and improved traction and mobility over rough
- 33) 12V-14AH maintenance free battery included
- 34) Accessories included: Wheel kits, 1.0Qt start up engine oil, DC charging cables, Sparkplug socket, Owner's Manual

Open Fram Gasoline Portable Generator

Model Number	SUA12000E
Starting Watts	12000
Running Watts	9000
UPC Code	851217006114
Alternator Brand	Senci
Automatic Voltage Regulator	Yes
AC Load	120/240V
Phase, Frequency	Single, 60Hz
Engine (OHV)	459cc/16hp
Starting Method	E-start
Lubrication Method	Splash
Low Oil Shut Down Method	Automatic
Running VAC Amperage	37.5A
LCD Hour meter	Yes
Direct Circuit (DC)	Yes
Low Oil Alert Lamp	1
Circuit Breaker	8.3A, 20A, 30A, 38A
120V 20A NEMA 5-20R Outlet	4 GFCI
120V 30A NEMA L5-30R Outlet	1
120/240V 50A NEMA L14-50R Outlet	1
Weather Protected Outlet Cover	4
Neutral Bonded to Frame	Yes
Fuel Tank Capacity	7Gal. (25L)
Run time @ 50% Load (Hrs)	9
Run time @ 100% Load (Hrs)	7
Built-in Fuel Gauge on Fuel Tank	Yes
Engine Oil Capacity (Qt. / L)	1.2Qt. (1.1L)
Recommended Oil	SAE 10W-30
Muffler with USDA Spark Arrestor	Yes
Noise Level, dBA at 23ft (7m)	78
Durable Tubular Steel Frame (Dia.)	1.25in. / 32mm
Fold-down Handle	Factory Built-in
Maintenance Free Battery	12V/14AH
Engine Oil Supplied	1.0Qt. 10W-30
DC Charging Cable	1
Spark Plug Socket	Yes
Wheel Kits	9.5-in. solid wheel
Warranty (Residential. / Commercial)	2 Year / 1 Year
Emission Certification	EPA Approved
Gross Weight (Lbs / kgs)	226Lbs/98kgs
Net Weight (Lbs / kgs)	215Lbs/93.5kgs
Assembly Dimension (LxWxH) (in.)	27.8 x 26.5 x 27.5
Packing Dimension (LxWxH) (in.)	28.5 x 21.5 x 25.5
Loading Q'ty (20GP/40GP) (Units)	90/180

Outlets:

- 1 - NEMA 120/240VAC 30A L14-30R Locking
- 1 - NEMA 120/240VAC 50A, 14-50R
- 1 - 12VDC 8.3A Adaptor Plug



GENERATORS PRESSURE WASHERS WATER PUMPS ENGINES SERVICE & SUPPORT.

A-iPower Corp. | Commerce Way Unit A | Fontanna, CA 92337 | 909-923-2068 | www.a-ipower.com