



Model Number **SUA9000E**

Powerful. Portable. Tough. Compact. Reliable. Purpose-Built



Features


- 1) 9,000 Starting Watts / 7,000 Running Watts
- 2) 60Hz, 120VAC / 240VAC, Single Phase
- 3) 420cc / 14HP OHV, single cylinder, air-cooled, 4-stroke engine with electric start
- 4) High performance alternator provides greater peak wattage which allows motor driven appliances and tools to operate simultaneously
- 5) Multiple Front Panel Outlets. Easy access, ergonomically angled compact control panel with multiple outlets with weather proof cover provides easy power connections and added protection from the environment and rugged working condition while conveniently providing easy, user-friendly access and visibility to the panel
- 6) Keyless one-touch push button provides an effortless start
- 7) Back-up recoil start. The oversized recoil ad ergonomically designed big grip reduces your effort to pull the recoil easily to start the engine.
- 8) Cast iron sleeves for engine durability and extended run life
- 9) Intelligent Automatic Voltage Regulator (AVR) helps minimize voltage fluctuations and deliver consistent stable power under load
- 10) 7.0 gallon, large heavy duty all steel construction fuel tank provides up to 9.5 hours of run time at 50% load
- 11) High quality, bright red, powder coat finish is attractive yet rustproof
- 12) Seamless welding prevents leakage while curved edges and corners provided added safety
- 13) Large built-in easy to read fuel gauge
- 14) Large Stainless steel fuel cap
- 15) Large counter-sink around fuel filling port prevents fuel overflow while filling
- 16) Fuel tank breather hose located beneath tank, provides added protection from accidental damage
- 17) GFCI Protected Outlets provides added protection and safety under damp condition
- 18) Digital Hour meter for monitoring runtimes and scheduling of maintenance intervals
- 19) Push to reset circuit breakers provide overload protection
- 20) Weather proof cover provides protection for Circuit breakers and receptacles
- 21) Built-in DC Adapter Plug. Built for charge your battery or use with your USB adapter to charge your cellphone. DC charging cable included
- 22) Low oil shut down automatically protect engine from potential damage
- 23) The cord protective cover keeps all the wires concealed while providing protection and neat appearance
- 24) Dual element air filter protects engine while allowing extended service interval
- 25) Rigid low tone muffler. Compact heavy duty reinforced steel muffler helps minimize the noise level. Equipped with USDA approved spark arrestor provides added safety.
- 27) Neutral bonded to frame for added safety
- 28) 1.1in dia. rigid tubular steel frame with attractive silver grey powder coat finish
- 29) Built-in ergonomically designed handle provides easy transportation and folds down for compact storage
- 30) Effortless Move. Large 9.5in never-flat wheels designed for heavy duty loads and improved traction
- 31) Easy to assemble and ready to go
- 32) Recommended Oil: SAE 10W-30
- 34) 12V-14AH maintenance free battery included
- 35) Accessories included: Wheel kits, 1.0Qt start up engine oil, DC charging cables, Sparkplug socket, Owner's Manual

Open Frame Gasoline Portable Generator

| | |
|--------------------------------------|---------------------|
| Model Number | SUA9000E |
| Starting Watts | 9000 |
| Running Watts | 7000 |
| UPC Code | 851217006107 |
| Alternator Brand | Senci |
| Automatic Voltage Regulator | Yes |
| AC Load | 120/240V |
| Phase, Frequency | Single, 60Hz |
| Engine (OHV) | 420cc/14hp |
| Starting Method | E-start |
| Lubrication Method | Splash |
| Low Oil Shut Down Method | Automatic |
| Running VAC Amperage | 29.1A |
| LCD Hour meter | Yes |
| DC Adapter Plug | Yes |
| Low Oil Alert Lamp | 1 |
| Circuit Breaker | 8.3A, 20A, 30A |
| 120V 20A NEMA 5-20R Outlet | 4 GFCI |
| 120V 30A NEMA L5-30R Outlet | 1 |
| 120/240V 30A NEMA L14-30R Outlet | 1 |
| Weather Protected Outlet Cover | 4 |
| Neutral Bonded to Frame | Yes |
| Fuel Tank Capacity | 7Gal. (25L) |
| Run time @ 50% Load (Hrs) | 9.5 |
| Run time @ 100% Load (Hrs) | 6.5 |
| Built-in Fuel Gauge on Fuel Tank | Yes |
| Engine Oil Capacity (Qt. / L) | 1.2Qt. (1.1L) |
| Recommended Oil | SAE 10W-30 |
| Muffler with USDA Spark Arrestor | Yes |
| Noise Level, dBA | 76 |
| Durable Tubular Steel Frame (Dia.) | 1.1in. / 28mm |
| Fold-down Handle | Factory Built-in |
| Maintenance Free Battery | 12V/14AH |
| Engine Oil Supplied | 1.0Qt. 10W-30 |
| DC Charging Cable | Yes |
| Spark Plug Socket | Yes |
| Wheel Kits | 9.5-in. solid wheel |
| Warranty (Residential. / Commercial) | 2 Year / 1 Year |
| Emission Certification | EPA |
| Gross Weight (Lbs / kgs) | 211Lbs/96kgs |
| Net Weight (Lbs / kgs) | 202Lbs/92kgs |
| Assembly Dimension (HxWxH) (in.) | 27.8x27.2x25.4 |
| Packing Dimension (HxWxH) (in.) | 28.9x21.7x24 |
| Loading Q'ty (20GP/40GP) | 96/192 |

Outlets:

- 4 - NEMA 120VAC 20A, GFCI protected
- 1 - NEMA 120VAC 30A L5-30R Locking
- 1 - NEMA 120/240VAC 30A L14-30R Locking
- 1 - 12VDC 8.3A Adaptor Plug



Note: The specifications or features of our product may vary from the list shown. A-iPower reserves the rights to change features, specifications without notice for future improvements of product.

