

Model# SUWP80

UPC Number: 616641364083





Suction / Discharge Port Diameter (in)	3" NTP (Thread Male)
Dischage Flow (gallons/minute)	223
Outlet / Inlet Connection	Threaded Male (NPT)
Horse Power (hp)	7HP / 208 CC OHV
Bore X Stroke	70 X 54 mm
Starting System	Manual
Pump Type	Self-Priming
Volute	Rigid Mounted Cast Iron
Impeller	4 Vane Cast Iron
Mechanical Seal	Silicon Carbide
Suction Head Lift	16.4 Ft. (5M)
Total Head Lift	85.3 Ft. (26M)
Flow	220 GPM (50m /3 min)
Head Pressure (ft)	88
Maximum Working Temperature (F)	180
Minimum Working Temperature (F)	45
DBA @ 7 Ft	75
Oil Capacity	0.16 Gal. (0.6L)
Fuel Capacity	0.95 Gal. (3.6L)
Run Time at 50% Load	4 Hrs
Housing Material	Aluminum
Frame Chassis	0.9 in (22mm)
Submersible	No
Hardware included	Yes
Adjustable Speed	No
Cord Length (Ft.(N/A
Assembled Length (in.)	19.7 in (500mm)
Assembled Width (in.)	15.7 in (400mm)
Assembled Height (in.)	15.7 in (400mm)
Product Length (in)	20.5 in (520mm)
Product Width (in)	16.5 in (420mm)
Product Height (in)	16.7 in (425mm)
Net Weight (No Packaging)	55 Lbs
Gross Weight (With Packaging)	59 Lbs
Load Quantity 40'/20' Container	560/280
Load Quantity 53' Trailer	
Pallet Quantity - 40" X 48"	
Warranty	

NOTES:
