

Sport Truck



PREMIUM LIMITED WARRANTY
FREE 45-DAY ROAD TEST!
DIRECTIONAL DESIGN
V-RATED

The XST is a premium all-season sport truck tire designed for drivers who want to upgrade their vehicles' looks and handling by replacing the original equipment wheels and tires. Get high performance from your SUV tire.

Fitments:
Harley Ford, Plus Fitments

UTQG		
TREAD WEAR	TRACTION	TEMP.
420	A	A

M+S Rated

**PERFORMANCE REINFORCED
TREAD COMPOUND**

The XST tread compound is specifically engineered to optimize all-around tire performance. Capitalizing on technology from our all-weather performance lines, this compound's unique polymer system provides solid wet and dry traction and allows ample snow capability. Additionally the compound is reinforced with performance grade carbon black, which balances traction and tread wear.

LATERALLY BIASED SHOULDER ELEMENTS

The shoulder element design effectively conducts water evacuation away from the contact area while combating irregular wear (heel and toe wear).

OPTIMIZED PITCH SEQUENCE BY SIZE

Industry-wide, typically, the same pitch sequence is applied throughout a tire line. But the Zeon XST varies the number of shoulder elements based on tire size, which reduces noise frequency, allowing a quiet ride in large diameter sizes.

TAPERED TREAD

This design feature puts deep tread in the center and slightly shallower tread in the shoulders. This puts more rubber down in the fastest wearing part of the tire, the center. The result is less weight and improved wet handling.

RIM PROTECTOR

A rubber rim protector extends beyond the rim flange and decreases the chance of rim damage that can occur if a tire/wheel assembly scuffs a curb.

SPIRAL WOUND NYLON OVERWRAP (S.N.O.W.)

Spiral wound nylon overwrap combats centrifugal force under high-speed applications. This ability inhibits tire growth and maintains stability and carcass integrity.

PERFORMANCE APEX

The hardened rubber compound, or bead filler, above the bead minimizes sidewall flex in cornering. The result is crisp handling.

ALWAYS CONSULT AND FOLLOW THE VEHICLE MANUFACTURERS' REPLACEMENT TIRE RECOMMENDATIONS AND WARNINGS. Use the information on the vehicle placard and vehicle owner's manual to identify original equipment air pressure, tire size, speed rating and load capacity. Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation. Contact your Cooper dealer or Cooper Tire for current information.



Item #	Tire Size & Service Description		Meas. Rim Wdth / Approved Rim Width	PSI	Pass Max Load	LT Max Load	Overall Diam.	Sect. Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm		Ship Wt lbs. kilo		Size Code	UPC
COOPER ZEON XST black sidewall sizes:															W11-4JY	
04071	285/50R20XL	116V	(9.0) 8.0-10.0	50	2756	2508	31.13	11.92	9.93	648	12	9.5	49	22.2	HR06	029142628446
04082	275/45R20XL	110V	(9.0) 8.5-10.0	50	2337	2127	29.64	10.97	9.25	680	12	9.5	44	20.0	JY06	029142628460