


## DGC80/DR908



### Performance:

- < Circumferential grooves are better for high - speed driving . unique narrow grooves design effectively prevents stones lodged in the tread.
- < Big pattern groove on shoulder provides good grip on dry , wet and mud road conditions.
- < Excellent wear-resistant tread compound can improve puncture resistance , tear resistance and mileage effectively.

### On/Off use

SIZE	PR	Pattern	LI/SS	Type	Standard Rim	Permitted Rim	Tread Depth (mm)	Max. load Single (KG)	Max. load Dual (KG)	Max. pressure Single (kPa)	Max. pressure Dual (kPa)
6.50R16	12	DR908	110/105L	TT	5.50F	5.00E5.00F	10.5	1060	905	670	670
7.00R16	14	DR908	118/114L	TT	5.50F	6.00G	11	1320	1180	770	770
7.50R16	14	DR908	122/118L	TT	6.0G	5.50F/6.50H	13	1500	1320	770	770
M7.50R16	14	DR908	122/118M	TT	6.0G	---	13	1500	1320	770	770
8.25R16	16	DR908	128/124L	TT	6.50H	6.00G/6.5	13	1800	1600	770	770
M8.25R16	16	DR908	128/124M	TT	6.50H	6.00G	13	1800	1600	770	770
8.25R20	16	DR908	139/137K	TT	6.5	6.50T 7.0 7.00T	15	2430	2300	930	930
9.00R20	16	DR908	144/142K	TT	7.0	7.00T 7.5	15.5	2800	2650	900	900
10.00R20	16	DR908	146/143K	TT	7.5	7.50V 8.0	16	3000	2725	830	830
10.00R20	18	DR908	149/146K	TT	7.5	7.50V 8.0	16	3250	3000	930	930
10.00R20	18	DGC80	149/146K	TT	7.5	7.50V 8.0	16	3250	3000	930	930
11.00R20	18	DR908	152/149K	TT	8.0	8.00V 8.5	17	3550	3250	930	930
11R22.5	16	DR908	148/145M	TL	8.25	7.50	15	3150	2900	840	840
11R24.5	16	DR908	149/146M	TL	8.25	7.50	15	3250	3000	830	830
12.00R20	18	DR908	154/151K	TT	8.5	8.50V/9.0	17.5	3750	3450	830	830
12.00R20	18	DGC80	154/151K	TT	8.5	8.50V/9.0	17.5	3750	3450	830	830
12R22.5	18	DR908	152/149L	TL	9.00	8.25	17	3550/3250	3250	930	930
12.00R24	20	DGC80	160/157K	TT	8.5	8.50V 9.00	16	4500	4125	900	900
13R22.5	18	DR908	154/151L	TL	9.75	9.00	17.5	3750	3450	830	830
295/80R22.5	16	DR908	152/148M	TL	9.00	8.25	15	3550	3150	830	830
295/80R22.5	18	DR908	152/149M	TL	9.00	8.25	15	3550	3250	900	900
315/80R22.5	18	DR908	154/150M	TL	9.00	9.75	15	3750	3350	850	850
315/80R22.5	20	DGC80	161/154 K	TL	9.00	9.75	15	4625	3750	900	900

# DGQ30/DR930



## Performance:

- < Robust tread blocks provide high resistance to lacerations;
- < Transversal groove arrangement promotes excellent traction in high severity conditions;
- < Wide and deep cross grooves reduce stone trapping and enhance selfcleaning capability;

### Quarry&Mine

SIZE	PR	Pattern	LI/SS	Type	Standard Rim	Permitted Rim	Tread Depth (mm)	Max. load Single (KG)	Max. load Dual (KG)	Max. pressure Single (kPa)	Max. pressure Dual (kPa)
7.50R16	14	DGQ30	122/118J	TT	6.00G	5.50F/6.50H	18	1500	1320	770	770
10.00R20	18	DGQ30	149/146G	TT	7.5	7.50V 8.0	23.5	3250	3000	930	930
11R22.5	16	DGQ30	146/143G	TL	8.25	7.50	23	3000	2725	830	830
11R24.5	16	DR930	149/146G	TL	8.25	7.50	23	3250	3000	830	830
12.00R20	20	DGQ30	156/153F	TT	8.5	8.50V/9.0	21.5	4000	3650	900	900
12R22.5	18	DR930	152/149G	TL	9.00	8.25	23	3550	3250	930	930
12.00R24	20	DGQ30	160/157F	TT	8.5	8.50V 9.00	23	4500	4125	900	900
295/80R22.5	18	DR930	152/149J	TL	9.00	8.25	23	3550	3250	900	900
315/80R22.5	20	DR930	156/151L	TL	9.00	9.75	21	4000	3450	850	850

# **CONTACT INFORMATION**

Email:

APAC [suyun.zhao@aeolustyre.biz](mailto:suyun.zhao@aeolustyre.biz)

MEA [bingxiang.li@aeolustyre.biz](mailto:bingxiang.li@aeolustyre.biz)

E.U. [linjie.wen@aeolustyre.biz](mailto:linjie.wen@aeolustyre.biz)

CIS [ning.gao@aeolustyre.biz](mailto:ning.gao@aeolustyre.biz)

NAFTA [kunpei.shi@aeolustyre.biz](mailto:kunpei.shi@aeolustyre.biz)

LATAM [wei.li@aeolustyre.biz](mailto:wei.li@aeolustyre.biz)



**DOUBLE HAPPINESS**