



## DSL90/DR909



### Performance:

- < Steer wheel, long distance application
- < Suitable for high speed on good road surface
- < With good drainage and anti-side-skid character
- < Low noise and low rolling resistance
- < Excellent high speed performance

#### long haul

SIZE	PR	Pattern	LI/SS	Type	Standard Rim	Permitted Rim	Tread Depth (mm)	Max. load Single (KG)	Max. load Dual (KG)	Max. pressure Single (kPa)	Max. pressure Dual (kPa)
9R22.5	14	DR909	136/134M	TL	6.75	6.00/7.50	14	2240	2120	830	830
11R22.5	16	DR909	148/145M	TL	8.25	7.50	15	3150	2900	840	840
11R24.5	16	DR909	149/146M	TL	8.25	7.50	15	3250	3000	830	830
12R22.5	18	DR909	152/149L	TL	9.00	8.25	15.5	3550	3250	930	930
295/80R22.5	16	DR909	152/148M	TL	9.00	8.25	15.5	3550	3150	830	830
295/80R22.5	18	DR909	154/152M	TL	9.00	8.25	15.5	3750	3550	900	900
315/80R22.5	20	DR909	156/151M	TL	9.00	9.75	15	4000	3450	850	850
315/80R22.5	20	DSL90	156/151M	TL	9.00	9.75	15	4000	3450	850	850



## DR919



### Performance:

- < Four groove design , will reduce the rolling resistance of tyres , fuel-efficient up to 3-5% more than regular pattern.
- < Has good control performance and steering performance , ensure safer driving.
- < Widen tread design , has the good stability and wear resistance . unique formula , high wear resistance and low heat generating , greatly improves the service life of tires.

#### long haul

SIZE	PR	Pattern	LI/SS	Type	Standard Rim	Permitted Rim	Tread Depth (mm)	Max. load Single (KG)	Max. load Dual (KG)	Max. pressure Single (kPa)	Max. pressure Dual (kPa)
275/70R22.5	18	DR919	148/145M	TL	8.25	9.00	14	3150	2900	900	900
315/70R22.5	18	DR919	154/150L	TL	9.00	9.75	14.5	3750	3350	850	850

# DGQ30/DR930



## Performance:

- < Robust tread blocks provide high resistance to lacerations;
- < Transversal groove arrangement promotes excellent traction in high severity conditions;
- < Wide and deep cross grooves reduce stone trapping and enhance selfcleaning capability;

### Quarry&Mine

SIZE	PR	Pattern	LI/SS	Type	Standard Rim	Permitted Rim	Tread Depth (mm)	Max. load Single (KG)	Max. load Dual (KG)	Max. pressure Single (kPa)	Max. pressure Dual (kPa)
7.50R16	14	DGQ30	122/118J	TT	6.00G	5.50F/6.50H	18	1500	1320	770	770
10.00R20	18	DGQ30	149/146G	TT	7.5	7.50V 8.0	23.5	3250	3000	930	930
11R22.5	16	DGQ30	146/143G	TL	8.25	7.50	23	3000	2725	830	830
11R24.5	16	DR930	149/146G	TL	8.25	7.50	23	3250	3000	830	830
12.00R20	20	DGQ30	156/153F	TT	8.5	8.50V/9.0	21.5	4000	3650	900	900
12R22.5	18	DR930	152/149G	TL	9.00	8.25	23	3550	3250	930	930
12.00R24	20	DGQ30	160/157F	TT	8.5	8.50V 9.00	23	4500	4125	900	900
295/80R22.5	18	DR930	152/149J	TL	9.00	8.25	23	3550	3250	900	900
315/80R22.5	20	DR930	156/151L	TL	9.00	9.75	21	4000	3450	850	850

# **CONTACT INFORMATION**

Email:

APAC [suyun.zhao@aeolustyre.biz](mailto:suyun.zhao@aeolustyre.biz)

MEA [bingxiang.li@aeolustyre.biz](mailto:bingxiang.li@aeolustyre.biz)

E.U. [linjie.wen@aeolustyre.biz](mailto:linjie.wen@aeolustyre.biz)

CIS [ning.gao@aeolustyre.biz](mailto:ning.gao@aeolustyre.biz)

NAFTA [kunpei.shi@aeolustyre.biz](mailto:kunpei.shi@aeolustyre.biz)

LATAM [wei.li@aeolustyre.biz](mailto:wei.li@aeolustyre.biz)

