

## DR938



### Performance:

- < Drive wheel, regional use
- < Suitable for highway on good condition
- < With good grip and traction character
- < Good anti-wearing character, long mileage

### Regional

SIZE	PR	Pattern	LI/SS	Type	Standard Rim	Permitted Rim	Tread Depth (mm)	Max. load Single (KG)	Max. load Dual (KG)	Max. pressure Single (kPa)	Max. pressure Dual (kPa)
12R22.5	18	DR938	152/149L	TL	9.00	8.25	21	3550	3250	930	930
315/80R22.5	20	DR938	156/151G	TL	9.00	9.75	23	4000	3450	850	850

## DR905



### Performance:

- < Trailer wheel for regional use;
- < With excellent anti-side-skid character;
- < Low rolling resistance character, low noise;
- < With excellent anti-side-skid and low heat generating character.

### Regional

SIZE	PR	Pattern	LI/SS	Type	Standard Rim	Permitted Rim	Tread Depth (mm)	Max. load Single (KG)	Max. load Dual (KG)	Max. pressure Single (kPa)	Max. pressure Dual (kPa)
385/65R22.5	20	DR905	160K	TL	11.75	12.25	16	4500		900	
425/65R22.5	20	DR905	165K	TL	13	12.25	16	5150		825	

# DGQ30/DR930



## Performance:

- < Robust tread blocks provide high resistance to lacerations;
- < Transversal groove arrangement promotes excellent traction in high severity conditions;
- < Wide and deep cross grooves reduce stone trapping and enhance selfcleaning capability;

### Quarry&Mine

SIZE	PR	Pattern	LI/SS	Type	Standard Rim	Permitted Rim	Tread Depth (mm)	Max. load Single (KG)	Max. load Dual (KG)	Max. pressure Single (kPa)	Max. pressure Dual (kPa)
7.50R16	14	DGQ30	122/118J	TT	6.00G	5.50F/6.50H	18	1500	1320	770	770
10.00R20	18	DGQ30	149/146G	TT	7.5	7.50V 8.0	23.5	3250	3000	930	930
11R22.5	16	DGQ30	146/143G	TL	8.25	7.50	23	3000	2725	830	830
11R24.5	16	DR930	149/146G	TL	8.25	7.50	23	3250	3000	830	830
12.00R20	20	DGQ30	156/153F	TT	8.5	8.50V/9.0	21.5	4000	3650	900	900
12R22.5	18	DR930	152/149G	TL	9.00	8.25	23	3550	3250	930	930
12.00R24	20	DGQ30	160/157F	TT	8.5	8.50V 9.00	23	4500	4125	900	900
295/80R22.5	18	DR930	152/149J	TL	9.00	8.25	23	3550	3250	900	900
315/80R22.5	20	DR930	156/151L	TL	9.00	9.75	21	4000	3450	850	850

# **CONTACT INFORMATION**

Email:

APAC [suyun.zhao@aeolustyre.biz](mailto:suyun.zhao@aeolustyre.biz)

MEA [bingxiang.li@aeolustyre.biz](mailto:bingxiang.li@aeolustyre.biz)

E.U. [linjie.wen@aeolustyre.biz](mailto:linjie.wen@aeolustyre.biz)

CIS [ning.gao@aeolustyre.biz](mailto:ning.gao@aeolustyre.biz)

NAFTA [kunpei.shi@aeolustyre.biz](mailto:kunpei.shi@aeolustyre.biz)

LATAM [wei.li@aeolustyre.biz](mailto:wei.li@aeolustyre.biz)

