



**Model Number SUA5000**

Powerful, Portable, Tough, Compact, Reliable, Purpose-Built

4250 Running Watts  
5000 Starting Watts  
120/240VAC



**Features**

- 1) 5,000 Starting Watts / 4,250 Running Watts
- 2) 60Hz, 120VAC / 240VAC, Single Phase
- 3) 223cc / 7.5HP OHV, single cylinder, air-cooled, 4-stroke engine with manual start
- 4) High performance alternator provides greater peak wattage which allows motor-driven appliances and tools to operate simultaneously
- 5) Easy access, ergonomically angled compact control panel with multiple outlets with weather proof cover provides easy power connections and added protection from the environment and rugged working condition while conveniently providing easy, user-friendly access and visibility to the panel
- 6) Effortless start. The oversized recoil and ergonomically designed big grip reduces your effort to pull the recoil easily to start
- 7) Cast iron sleeves for engine provide durability and extended run life
- 8) Intelligent Automatic Voltage Regulator (AVR) minimize voltage fluctuations and deliver consistent stable power under load
- 9) 4.0 gallon, large heavy duty all steel construction fuel tank provides up to 9 hours of run time at 50% load
- 10) High quality, bright red, powder coat finish is attractive yet rustproof
- 11) Seamless welding prevents leakage while curved edges and corners provided added safety
- 12) Large built-in easy to read fuel gauge
- 13) Large Stainless steel fuel cap
- 14) Large counter-sink around fuel filling port prevents fuel overflow while filling
- 15) Fuel tank breather hose located beneath tank, provides added protection from accidental damage
- 16) Digital Hour meter for monitoring runtimes and scheduling of maintenance intervals
- 17) Push to reset circuit breakers provide overload protection
- 18) *Weather proof cover provides protection for circuit breakers and receptacles*
- 19) *Built-in DC Adapter Plug. Built for charge your battery or use with your USB adapter to charge your cellphone. DC charging cable included.*
- 20) RV Ready. This generator is built for your convenience when RVing. A free 30A RV adaptor included.
- 21) Low oil shut down automatically protects engine from potential damage
- 22) Dual element air filter protects engine while allowing extended service interval
- 23) Rigid low tone muffler. Compact heavy duty reinforced steel muffler helps minimize the noise level. Equipped with USDA approved spark arrestor provides added safety.
- 23) *GFCI Protected Outlets provides added protection and safety under damp condition*
- 24) 68dBA at 23ft sound rating
- 25) *Neutral bonded to frame for added safety*
- 26) 1.0in. dia. rigid tubular steel frame with attractive silver grey powder coat finish
- 27) Built-in ergonomically designed handle provides easy transportation and folds down for compact storage
- 28) Effortless Move. 7.0in never-flat wheels designed for heavy duty loads and improved traction and mobility over rough terrain, ultimate portability
- 29) Easy to assemble and ready to go
- 30) Recommended Oil: SAE 10W-30
- 31) Warranty: 2-Year Residential / 1-Year Commercial (First Year Parts & Labor / Second Year Parts Only)
- 32) EPA / 49 States. Not for sale in California
- 41) *Accessories included: Wheel kits, 0.6Qt start up engine oil, DC charging cables, Sparkplug socket, RV adapter, Owner's Manual*




Gasoline Portable Generators	
Model Number	SUA5000
Starting Watts	5000
Running Watts	4250
UPC Code	851217006084
Aternator Brand	Senci
Automatic Voltage Regulator	Yes
AC Load	120/240V
Phase, Frequency	Single, 60Hz
Engine (OHV)	223cc/7.5hp
Starting Method	Manual
Lubrication Method	Splash
Low Oil Shut Down Method	Automatic
Running VAC Amperage	17.7A
LCD Hour meter	Yes
DC Adapter Plug	Yes
Low Oil Alert Lamp	1
Circuit Breaker	8.3A, 20A, 30A
120V 20A NEMA Outlet	2 GFCI
120V 30A NEMA L5-30R Outlet	1
120/240V 30A NEMA L14-30R Outlet	1
Weather Protected Outlet Cover	3
Neutral Bonded to Frame	Yes
Fuel Tank Capacity	4Gt. (15L)
Run time @ 50% Load (Hrs)	9
Run time @ 100% Load (Hrs)	6
Built-in Fuel Gauge on Fuel Tank	Yes
Engine Oil Capacity (Qt. / L)	0.6Qt. (0.6L)
Recommended Oil	SAE 10W-30
Muffler with USDA Spark Arrestor	Yes
Noise Level, dBA at 23ft (7m)	68
Durable Tubular Steel Frame (Dia.)	1.0in. / 25mm
Fold-down Handle	Factory Built-in
Engine Oil Supplied	0.6Qt. 10W-30
DC Charging Cable	1
RV Adaptor	1
Spark Plug Socket	Yes
Wheel Kits	7-in. solid wheel
Warranty (Residential. / Commercial)	2 Year / 1 Year
Emission Certification	EPA
Gross Weight (Lbs / kgs)	130Lbs/59kgs
Net Weight (Lbs / kgs)	123Lbs/54kgs
Assembly Dimension (HxWxD) (in.)	24.4x22.8x22.6
Packing Dimension (HxWxD) (in.)	25.4x19x21.6
Loading Qty (20GP/40GP)	164/336

**Unit Price FOB**

**Outlets:**

- 2 - NEMA 120VAC 20A, GFCI protected
- 1 - NEMA 120VAC 30A L5-30R Locking
- 1 - NEMA 120/240VAC 30A L14-30R Locking
- 1 - 12VDC 8.3A Adaptor Plug



**Note:** The specifications or features of our product may vary from the list shown. A-iPower reserves the rights to change features, specifications without notice for future improvements of product.

