



Model Number SUA7000C

Powerful, Portable, Tough, Compact, Reliable, Purpose-Built



Features

- 7,000 Starting Watts / 6,000 Running Watts
- 60Hz, 120VAC / 240VAC, Single Phase
- 389cc / 13HP OHV, single cylinder, air-cooled, 4-stroke engine with manual start
- High performance alternator provides greater peak wattage which allows motor driven appliances and tools to operate
- Easy access, ergonomically angled compact control panel with multiple outlets with weather proof cover provides easy power connections and added protection from the environment and rugged working condition while conveniently providing easy, user-friendly access and visibility to the panel
- Effortless start. The oversized recoil and ergonomically designed big grip reduces your effort to pull the recoil easily to start the engine.
- Cast iron sleeves for engine durability and extended run time
- Intelligent Automatic Voltage Regulator (AVR) helps minimize voltage fluctuations and deliver consistent stable power
- 7.0 gallon, large heavy duty all steel construction fuel tank provides up to 12 hours of run time at 50% load
- High quality, bright red, powder coat finish is attractive yet rustproof
- Seamless welding prevents leakage while curved edges and corners provided added safety
- Large built-in easy to read fuel gauge
- Large Stainless steel fuel cap
- Large counter-sink around fuel filling port prevents fuel overflow while filling
- Fuel tank breather hose located beneath tank, provides added protection from accidental damage
- GFCI Protected Outlets provides added protection and safety under damp condition
- Digital Hour meter for monitoring runtimes and scheduling of maintenance intervals
- Push to reset circuit breakers provide overload protection
- Weather proof cover provides protection for circuit breakers and receptacles
- Built-in DC Adapter Plug. Built for charge your battery or use with your USB adapter to charge your cellphone.
- Low oil shut down automatically protects engine from potential damage
- Dual element air filter protects engine while allowing extended service interval
- Rigid low tone muffler. Compact heavy duty reinforced steel muffler helps minimize the noise level. Equipped with USDA approved spark arrestor provides added safety.
- Neutral bonded to frame for added safety
- 1.1in dia. rigid tubular steel frame with attractive silver grey powder coat finish
- Built-in ergonomically designed handle provides easy transportation and folds down for compact storage
- Effortless Move. Large 9.5in never-flat wheels designed for heavy duty loads
- Accessories included: Wheel kits, 1.0Qt start up engine oil, DC charging cables, Sparkplug socket, Owen's manual

Open Frame Gasoline Portable Generator

Model Number	SUA7000C
Starting Watts	7000
Running Watts	6000
UPC Code	851217006541
Alternator Brand	Senci
Automatic Voltage Regulator	Yes
AC Load	120/240V
Phase, Frequency	Single, 60Hz
Engine (OHV)	389cc/13hp
Starting Method	Manual
Lubrication Method	Splash
Low Oil Shut Down Method	Automatic
Running VAC Amperage	25A
LCD Hour meter	Yes
Direct Circuit (DC)	Yes
Low Oil Alert Lamp	1
Circuit Breaker	8.3A, 2-20A, 2P-25A
120V 20A NEMA 5-20R Outlet	4-GFCI
120/240V 30A NEMA L14-30R Outlet	1
Weather Protected Outlet Cover	3
Neutral Bonded to Frame	Yes
Fuel Tank Capacity	7Gal. (25L)
Run time @ 50% Load (Hrs)	12
Run time @ 100% Load (Hrs)	8
Built-in Fuel Gauge on Fuel Tank	Yes
Engine Oil Capacity (Qt. / L)	1.2Qt. (1.1L)
Recommended Oil	SAE 10W-30
Muffler with USDA Spark Arrestor	Yes
Noise Level, dBA at 23ft (7m)	74
Durable Tubular Steel Frame (Dia.)	1.1in. / 28mm
Fold-down Handle	Factory Built-in
Engine Oil Supplied	1.0Qt. 10W-30
DC Charging Cable	1
Spark Plug Socket	Yes
Wheel Kits	9.5-in. solid wheel
Warranty (Residential. / Commercial)	2 Year / 1 Year
Emission Certification	EPA / CARB Certified
Gross Weight (Lbs / kgs)	206Lbs/93.5kgs
Net Weight (Lbs / kgs)	195Lbs/88.5kgs
Assembly Dimension (LxWxH) (in.)	27.5 x 24.6 x 25.8
Packing Dimension (LxWxH) (in.)	28.7x22x24.4
Loading Q'ty (20GP/40GP)	96/192

Outlets:

- 4 - NEMA 120VAC 20A, GFCI protected
- 1 - NEMA 120/240VAC 30A L14-30R Locking
- 1 - 12VDC 8.3A Adaptor Plug

